

THIS SHEET IS PART OF THE DOCUMENT SET AND SHOULD NOT BE SEPARATED. ALWAYS REFER TO THE LATEST DRAWING SET.

EXISTING OVERHEAD DOOR SCHEDULE						
#	TYPE	MATERIAL	SIZE		COMMENTS	
			WIDTH	HEIGHT		
CH1	DT9.1	ALUMINUM	8'-0"	8'-0"	SEE PRODUCT APPROVAL FL 11734.26	
CH2	DT9.1	ALUMINUM	8'-0"	8'-0"	SEE PRODUCT APPROVAL FL 11734.26	
CH3	DT9.1	ALUMINUM	8'-0"	8'-0"	SEE PRODUCT APPROVAL FL 11734.26	

HAGER	241F DOME STOP	626	--	--	--	OR APPROV
HAGER	241F DOMES TOP	626		(3) 308D	GRAY	3

- 1 DOOR FRAMES SHALL BE SECURED RIGIDLY IN PLACE AND BRACED TO FLOOR AND STRUCTURE ABOVE TO PREVENT BREAK OUT TO PARTITIONS.
- 2 DOORS SHALL OPERATE FREELY WITHOUT BINDING.
- 3 SEE PLAN FOR DOOR SWING DIRECTIONS.
- 4 DOOR UNDERCUTS SHALL BE KEPT TO A MINIMAL DIMENSION AND SHALL BE UNIFORM THROUGHOUT PROJECT, UNLESS OTHERWISE NOTED.
- 5 DOOR FRAME THICKNESS SHALL FIT WALL THICKNESS, CONTRACTOR TO VERIFY WALL THICKNESS IN FIELD & COORDINATE WITH SUPPLIER AND ARCHITECT.
- 6 ALL GLAZING SHALL COMPLY W/ THE FLORIDA PROJECT APPROVAL DOCUMENTATION.
- 7 ALL STOREFRONT EXIT DOORS HAVE DECAL STATING: "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED" (FBC 1008.1.9.3 & 2.2).
- 8 DOOR FINISH TO BE DETERMINED BY OWNER.
- 9 CONFIRM ALL LOCKSETS & DOOR OPERATORS WITH OWNER PRIOR TO ORDERING.
- 10 CONTRACTOR SHALL COORDINATE KEYING OF LOCKS WITH OWNER UPON SUBSTANTIAL COMPLETION OF SPACE, BUDGET FOR THIS FUNCTION SHALL BE INCLUDED IN INITIAL BIDS.
- 11 ALL KEYPED LOCKS SUPPLIED ARE KEYPED DIFFERENTLY (TYP).
- 12 ALL HARDWARE SHALL BE UNLOCKED IN THE DIRECTION OF EGRESS, REGARDLESS OF OTHER LOCK FUNCTIONS.
- 13 ALL EXISTING DOOR HARDWARE TO REMAIN.
- 14 ALL DOOR HARDWARE TO HAVE "LEVER" TYPE HANDLES, COMPLIANT WITH ADA.
- 15 ALL DOOR HARDWARE TO COMPLY WITH SECTION 7.2.1.5 OF NFPA 101.

